

EzLogger Pro

EzLogger Pro is a self-developed monitoring device by GoodWe. In combination with a GoodWe solar inverter, it can easily read and record all key plant data and constantly transmit the data to the GoodWe portal via internet.



Communication distance up to 1000m



Connectivity for up to 60 devices at once



Data Breakpoint Resume



Encrypted Data Transmission Process

Communication management

Communication	Inverter communication	3 x RS485
	PC communication	10/100M Ethernet
	Wireless module (optional)	Wi-Fi; GPRS
Number of managed devices	RS485	60 (The number of devices connected to a single RS485 port shall not exceed 20)
Communication distance	RS485	1000m (shielded twisted pair wire shall be used)
	Ethernet	100m
	Wi-Fi	15m (reference value)
	GPRS	Not limited

General parameters

General parameters	Power adapter	Input: 100 ~ 240Vac, 50/60Hz, output: 12Vdc 1.5A
	Power consumption	General 3W, maximum 6W
	Storage capacity	16MB, expandable to 8GB through an optional SD card
	Dimensions (L * W * H)	190*118*37mm
	Weight	500g
	Operating temperature	-20°C ~ +60°C
	Relative humidity (no condensation)	5% ~ 95%
	IP rating	IP20
	Installation method	Wall mounting, table surface mounting, rail mounting
	Display	8 LED indicators